

RBRconcerto³ D.alti.tilt



The RBRconcerto³ D.alti.tilt is a unique data logger dedicated to total water depth. Equipped with a 3-axis tilt sensor and a 200kHz altimeter, the logger provides complete distance-to-surface and distance-to-bottom data. The instrument also includes a depth channel capable of both continuous and intermittent bursts. The RBRconcerto³ D.alti.tilt is available in a configuration that supports wave measurements up to 16Hz.

FEATURES



The following standard configurations are available:

- RBRconcerto³ D.alti.tilt
- ▶ RBRconcerto³ D.alti.tilt|wave16

pressure, 3-axis tilt, altimeter adds 16Hz wave measurements

The RBRconcerto³ D.alti.tilt makes it simple to configure the optimum sampling regime for your measurements. The large data storage capacity and fast download ability facilitate long deployments with higher sampling rates. The logger is available in a standard body or extended body with additional power for prolonged use. Dataset export to Matlab, Excel, OceanDataView[®], or text files makes post processing with your own algorithms effortless.



ALTITUDE, ATTITUDE, AND WAVE LOGGERS TOTAL WATER LEVEL INSTRUMENT

Specifications

Physical

Clock drift:±60 seconds/yearSize:346mm x Ø63.3mm (concerto)250mm x Ø25.4mm (solo)Weight:~1.4kg in air, 250g in waterDepth rating:750mSampling period:1s to 24hWave option: wave16 1, 2, 4, 8, or 16HzHousing:Plastic
--

Altitude

Range:	0.5 to 10m
Initial accuracy:	±0.01m
Frequency:	2MHz
Beamwidth:	~15°

Attitude

Accuracy:	±0.1°
Tilt:	3-Axis

Depth

Range:	20 / 50 / 100 / 200 / 500 / 750 dbar
Initial accuracy:	±0.05% FS (1cm)
Resolution:	0.001% FS
Time constant:	<0.01s
Typical stability:	0.1% FS per year

Options

- Wi-Fi communication
- Twist activation
- External data and power connector

RBR Ltd

95 Hines Road Ottawa, Ontario Canada K2K 2M5

+1 613 599 8900 info@rbr-global.com rbr-global.com